



Clearly the Right Choice

Products Designation	Design Pressure (DP)	Air Infiltration			Water Resistance					
		PSF	"H2O	MPH	PSF	"H2O	MPH	PSF	"H2O	MPH
R 15	15	1.57	(.30)	(25)	2.86	(0.55)	(33)	22.5	(4.33)	(94)
R 20	20	1.57	(.30)	(25)	3.00	(0.58)	(34)	30.0	(5.77)	(108)
R 25	25	1.57	(.30)	(25)	3.75	(0.72)	(38)	37.5	(7.21)	(121)
R 30	30	1.57	(.30)	(25)	4.50	(0.87)	(42)	45.0	(8.65)	(131)
R 35	35	1.57	(.30)	(25)	5.25	(1.01)	(45)	52.5	(10.10)	(143)
RC HC 40	40	1.57	(6.24)	(25)	6.00	(1.15)	(48)	60.0	(11.54)	(153)
RC HC 45	45	1.57	(6.24)	(25)	6.75	(1.30)	(51)	67.5	(12.98)	(162)
RC HC 50	50	1.57	(6.24)	(25)	7.50	(1.44)	(54)	75.0	(14.42)	(171)
RC HC 55	55	1.57	(6.24)	(25)	8.25	(1.59)	(57)	82.5	(15.87)	(180)
RC HC 60	60	1.57	(6.24)	(25)	9.00	(1.73)	(59)	90.0	(17.31)	(187)
RC HC 65	65	1.57	(6.24)	(25)	9.75	(1.88)	(62)	97.5	(18.75)	(195)
RC HC 70	70	1.57	(6.24)	(25)	10.50	(2.01)	(64)	105.0	(20.20)	(203)
RC HC 75	75	1.57	(6.24)	(25)	11.25	(2.16)	(66)	112.5	(21.6)	(210)

Notes: Design Pressure=Performance Class 'H2O=0.192*PSF
 Structural Test Pressure=1.5*Design Pressure MPH=sqrt of (390.625*PSF)
 Water Resistance= 0.15*Design Pressure

www.mgmindustries.com