

**SERIES #6010 SLIDER XO or OX**

Egress Sq. Ft.

**WIDTH**

Minimum Opening Width, 20".  
Minimum Opening Height, 24".

Ground Level 5.0 Sq Ft. Above Ground Level 5.7 Sq Ft.  
Other Exceptions Could Apply Check With Your Local Codes Department.

		Call-Out	2/4	2/6	2/8	3/0	3/4	3/6	3/8	4/0	4/4	4/6	4/8	5/0	5/4	5/6	5/8	6/0
		IWD	27.5	29.5	31.5	35.5	39.5	41.5	43.5	47.5	51.5	53.5	55.5	59.5	63.5	65.5	67.5	71.5
Call-Out	IWD	Opening	9.750	10.750	11.750	13.750	15.750	16.750	17.750	19.750	21.750	22.750	23.750	25.750	27.750	28.750	29.750	31.750
3/0	35.500	30.000	2.0	2.2	2.4	2.9	3.3	3.5	3.7	4.1	4.5	4.7	4.9	5.4	5.8	6.0	6.2	6.6
3/2	37.500	32.000	2.2	2.4	2.6	3.1	3.5	3.7	3.9	4.4	4.8	5.1	5.3	5.7	6.2	6.4	6.6	7.1
3/4	39.500	34.000	2.3	2.5	2.8	3.2	3.7	4.0	4.2	4.7	5.1	5.4	5.6	6.1	6.6	6.8	7.0	7.5
3/6	41.500	36.000	2.4	2.7	2.9	3.4	3.9	4.2	4.4	4.9	5.4	5.7	5.9	6.4	6.9	7.2	7.4	7.9
3/8	43.500	38.000	2.6	2.8	3.1	3.6	4.2	4.4	4.7	5.2	5.7	6.0	6.3	6.8	7.3	7.6	7.9	8.4

H	4/0	47.500	42.000	2.8	3.1	3.4	4.0	4.6	4.9	5.2	5.8	6.3	6.6	6.9	7.5	8.1	8.4	8.7	9.3
E	4/2	49.500	44.000	3.0	3.3	3.6	4.2	4.8	5.1	5.4	6.0	6.6	7.0	7.3	7.9	8.5	8.8	9.1	9.7
I	4/4	51.500	46.000	3.1	3.4	3.8	4.4	5.0	5.4	5.7	6.3	6.9	7.3	7.6	8.2	8.9	9.2	9.5	10.1
G	4/6	53.500	48.000	3.3	3.6	3.9	4.6	5.3	5.6	5.9	6.6	7.3	7.6	7.9	8.6	9.3	9.6	9.9	10.6
H	4/8	55.500	50.000	3.4	3.7	4.1	4.8	5.5	5.8	6.2	6.9	7.6	7.9	8.2	8.9	9.6	10.0	10.3	11.0
T	5/0	59.500	54.000	3.7	4.0	4.4	5.2	5.9	6.3	6.7	7.4	8.2	8.5	8.9	9.7	10.4	10.8	11.2	11.9
	5/2	61.500	56.000	3.8	4.2	4.6	5.3	6.1	6.5	6.9	7.7	8.5	8.8	9.2	10.0	10.8	11.2	11.6	12.3
	5/4	63.500	58.000	3.9	4.3	4.7	5.5	6.3	6.7	7.1	8.0	8.8	9.2	9.6	10.4	11.2	11.6	12.0	12.8
	5/6	65.500	60.000	4.1	4.5	4.9	5.7	6.6	7.0	7.4	8.2	9.1	9.5	9.9	10.7	11.6	12.0	12.4	13.2
	5/8	67.500	62.000	4.2	4.6	5.1	5.9	6.8	7.2	7.6	8.5	9.4	9.8	10.2	11.1	11.9	12.4	12.8	13.7
	6/0	71.500	66.000	4.5	4.9	5.4	6.3	7.2	7.7	8.1	9.1	10.0	10.4	10.9	11.8	12.7	13.2	13.6	14.6

IWD = Interior Window Dimension

DLO = Day Light Opening.

		WIDTH																	
DLO (XorO)		Call-Out	2/4	2/6	2/8	3/0	3/4	3/6	3/8	4/0	4/4	4/6	4/8	5/0	5/4	5/6	5/8	6/0	
		IWD	27.5	29.5	31.5	35.5	39.5	41.5	43.5	47.5	51.5	53.5	55.5	59.5	63.5	65.5	67.5	71.5	
Call-Out	IWD	Opening	10.000	11.000	12.000	14.000	16.000	17.000	18.000	20.000	22.000	23.000	24.000	26.000	28.000	29.000	30.000	32.000	
H	3/0	35.500	30.063	2.1	2.3	2.5	2.9	3.3	3.5	3.8	4.2	4.6	4.8	5.4	5.8	6.1	6.3	6.7	
G	4/0	47.500	42.063	2.9	3.2	3.5	4.1	4.7	5.0	5.3	5.8	6.4	6.7	7.0	7.6	8.2	8.5	8.8	9.3
H	5/0	59.500	54.063	3.8	4.1	4.5	5.3	6.0	6.4	6.8	7.5	8.3	8.6	9.0	9.8	10.5	10.9	11.3	12.0
T	6/0	71.500	66.063	4.6	5.0	5.5	6.4	7.3	7.8	8.3	9.2	10.1	10.6	11.0	11.9	12.8	13.3	13.8	14.7

\*\*\*\* Day Light Opening: Given for "X" (Moving) or "O" (Stationary), Double for total DLO.