

EGRESS

Series 8065, 8080 and 8067 Double Hung

Block and Tackle Balance

WIDTH

| Egress | | Call-Out | 2/0 | 2/4 | 2/6 | 2/8 | 3/0 | 3/4 | 3/6 | 3/8 | 4/0 |
|---------------|---------|----------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| | | IWD | 23.375 | 27.375 | 29.375 | 31.375 | 35.375 | 39.375 | 41.375 | 43.375 | 47.375 |
| Call-Out | IWD | Opening | 18.875 | 22.875 | 24.875 | 26.875 | 30.875 | 34.875 | 36.875 | 38.875 | 42.875 |
| 3/0 | 13.7500 | 0.5 | 0.07 | 0.08 | 0.09 | 0.09 | 0.11 | 0.12 | 0.13 | 0.13 | 0.15 |
| 3/2 | 15.7500 | 1.5 | 0.20 | 0.24 | 0.26 | 0.28 | 0.32 | 0.36 | 0.38 | 0.40 | 0.45 |
| 3/4 | 17.7500 | 2.5 | 0.33 | 0.40 | 0.43 | 0.47 | 0.54 | 0.61 | 0.64 | 0.67 | 0.74 |
| 3/6 | 19.7500 | 3.5 | 0.46 | 0.56 | 0.60 | 0.65 | 0.75 | 0.85 | 0.90 | 0.94 | 1.04 |
| 3/8 | 21.7500 | 4.5 | 0.59 | 0.71 | 0.78 | 0.84 | 0.96 | 1.09 | 1.15 | 1.21 | 1.34 |

| | | | | | | | | | | | | |
|----------|-----|---------|-------|------|------|------|------|------|------|------|------|------|
| H | 4/0 | 47.2500 | 17.25 | 2.26 | 2.74 | 2.98 | 3.22 | 3.70 | 4.18 | 4.42 | 4.66 | 5.14 |
| E | 4/2 | 49.2500 | 18.25 | 2.39 | 2.90 | 3.15 | 3.41 | 3.91 | 4.42 | 4.67 | 4.93 | 5.43 |
| I | 4/4 | 51.2500 | 19.25 | 2.52 | 3.06 | 3.33 | 3.59 | 4.13 | 4.66 | 4.93 | 5.20 | 5.73 |
| G | 4/6 | 53.2500 | 20.25 | 2.65 | 3.22 | 3.50 | 3.78 | 4.34 | 4.90 | 5.19 | 5.47 | 6.03 |
| H | 4/8 | 55.2500 | 21.25 | 2.79 | 3.38 | 3.67 | 3.97 | 4.56 | 5.15 | 5.44 | 5.74 | 6.33 |

| | | | | | | | | | | | | |
|----------|-----|---------|-------|------|------|------|------|------|------|------|------|------|
| T | 5/0 | 59.2500 | 23.25 | 3.05 | 3.69 | 4.02 | 4.34 | 4.99 | 5.63 | 5.95 | 6.28 | 6.92 |
| | 5/2 | 61.2500 | 24.25 | 3.18 | 3.85 | 4.19 | 4.53 | 5.20 | 5.87 | 6.21 | 6.55 | 7.22 |
| | 5/4 | 63.2500 | 25.25 | 3.31 | 4.01 | 4.36 | 4.71 | 5.41 | 6.12 | 6.47 | 6.82 | 7.52 |
| | 5/6 | 65.2500 | 26.25 | 3.44 | 4.17 | 4.53 | 4.90 | 5.63 | 6.36 | 6.72 | 7.09 | 7.82 |
| | 5/8 | 67.2500 | 27.25 | 3.57 | 4.33 | 4.71 | 5.09 | 5.84 | 6.60 | 6.98 | 7.36 | 8.11 |

| | | | | | | | | | | | | |
|--|-----|---------|-------|------|------|------|------|------|------|------|------|------|
| | 6/0 | 71.2500 | 29.25 | 3.83 | 4.65 | 5.05 | 5.46 | 6.27 | 7.08 | 7.49 | 7.90 | 8.71 |
| | 6/2 | 73.2500 | 30.25 | 3.97 | 4.81 | 5.23 | 5.65 | 6.49 | 7.33 | 7.75 | 8.17 | 9.01 |

20" Minimum Width.
24" Minimum Height.

5.0 SQ FT Ground Level
5.7 SQ FT Above Ground Level

Other Exceptions May Apply. Consult Your Local Codes Department.

IWD= Interior Window Dimension