


# MGM Industries, Inc.

## SERIES #5665 SINGLE HUNG

### 4 11/16" FULL VINYL JAMB TILT WINDOW



#### SPECIFICATIONS

Size Tested: AAMA101/I.S.2/A440-05 H-R65, 44" x 63"
Profiles: Main frame and sash components shall be constructed of extruded, high-impact-resistant and UV-stabilized, rigid polyvinyl chloride (PVC). Main frame shall be of multi-chambered design. Typical wall for extruded frame and sash shall be .062" or as indicated on the extrusion die drawings.
Fasteners: All screws and fastening devices shall be coated with Zinc or Cadmium.
Glass & Glazing: Overall 3/4" thick sealed insulating unit. Top glass interior drop, secured with perimeter bead. Vent is tilt type pocket sash mechanically fastened.
Weather-Stripping: All window gaps between main frame and sash members shall be weather-stripped to prevent air infiltration. Weather-strip shall be poly pile type with an integral polyethylene fin.
Finish: Members shall have an integral White, Tan or Earth-Tone color throughout the profile.
Hardware: All hardware components that come in contact with PVC shall be non-corrosive material.
Screens: All shall be half window type sufficient to cover the opening provided by the vent sash. Screen frames are 5/16" x 3/4" rolled formed aluminum. Screen fabric shall be 18x16 fiberglass mesh.

SUMMARY STRUCTURAL	IGU SUMMARY THERMAL
Aluminum Reinforced	U-Factor .33 (Low-E)
Air Infiltration: .01	SHGC .29 (Low-E)
Water: 9.75 psf	VT .58 (Low-E)
Load: 97.5 psf	R-Factor 3.03 (Low-E)